Complete Specifications

This page has been formatted for optimal printing. If you would like a printed copy of these features, click the "Print" button at the top of the browser window. Please note that this may require 12 or more pages.

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

EXTERIOR

	Coupe	Conv.	Z06
Appearance: – Clearcoat paint – Corrosion-proof body panels – Front license plate frame	X X O	X X O	X X O
Body moldings: – Body-side moldings	0	0	0
Headlamps: – Retractable halogen headlamps	X	x	x
<u>Lamps:</u> – Daytime Running Lamps – Dual halogen foglamps	x x	X X	X -
Mirrors, side: – Dual, electric, remote-control, heated sport mirrors	X	x	x
Top: – Manual convertible top with heated, glass rear window – One-piece removable roof panel – Transparent removable roof panel – Roof package with transparent and solid roof panels	x 0 0	X - - -	- - -
Windshield: – Solar-Ray tinted, flush-mounted glass	x	Х	x
Wipers: – Intermittent windshield wipers	x	x	x

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

INTERIOR

	Coupe	Conv.	Z06
Air bags: – Air bags (driver and passenger) with passenger-side on/off switch(1)	x	x	x
Air conditioner: – Air conditioning – Air conditioning (dual-zone with electronic control)	x x	x x	X X
Cargo: – Parcel net	x	х	-
Cargo shade: – Luggage shade	x	_	-
Console: – Console, lockable, storage with integral cup holder	x	Х	x
Convenience: – Memory Package (remembers presets for outside mirrors, radio, heater, defroster, air conditioning, power driver seat and, if so equipped, power telescoping steering column) – Twilight Sentinel	O(2) O	O(2) O	O(3) -
<u>Cruise:</u> – Cruise control	x	Х	x
Defogger: – Rear-window defogger	x	х	x
Floor covering: – Floor mats	x	х	X
Instrumentation:			

 Instrumentation, electric, analog Instrumentation, Head-Up Display 	X O(2)	X O(2)	X S
Key: – Remote Keyless Entry System	x	x	x
Locks: – PASS-Key theft-deterrent system with horn alarm – Power door locks	x x	X X	X X
Mirror(s), rearview: – Day/night rearview mirror with integral map light – Electrochromic mirrors (inside rearview/outside driver)	X O(2)	X O(2)	X O(4)
Mirror(s), vanity: – Illuminated dual visor mirrors	x	x	Х
Reminder chime: – Headlamps-on reminder – Turn signal-on reminder	X X	X X	X X
Steering column: – Power telescoping steering column – Tilt-Wheel steering column	O(2) X	O(2) X	- X
Windows: – Power windows with Express-Down feature	x	х	X

1 Corvette is equipped with a passenger Air Bag Off Switch for use when carrying children. Never place a rear-facing infant restraint in the front seat of any vehicle equipped with an active air bag. Always use safety belts and proper child restraints, even with air bags. See the Owner's Manual and child safety seat instructions for more safety information.

2 Requires optional Preferred Equipment Group 1SB.

3 Requires Electrochromic Mirrors.

4 Requires Memory Package.

ABACK TO TOP

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

SOUND SYSTEMS

	Coupe	Conv.	Z06
Sound:			
 – AM/FM stereo with CD player 	Х	Х	Х
– AM/FM stereo with cassette player and 12-disc remote CD			
changer	0	0	-
 – 12-disc remote CD changer 	0	0	_
 Bose audio and amplifier system 	Х	Х	Х
	-		,

BACK TO TOP

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

ENGINE/CHASSIS

	Coupe	Conv.	Z06	
Brakes:				
 Four-wheel disc antilock brake system (ABS) 	Х	Х	Х	
 Low tire pressure warning system 	Х	Х	-	
Differential:				
 Limited-slip differential 	Х	Х	Х	
Engine:				
 – 5.7 Liter LS1 V8 engine with Sequential Fuel Injection 	Х	Х	_	
- 5.7 Liter LS6 V8 engine with Sequential Fuel Injection	-	-	Х	
Exhaust system:				
- Stainless-steel exhaust system (aluminized stainless-steel rear of				
catalytic converter)	Х	Х	-	
 Titanium exhaust components (mufflers and tailpipes) 	-	-	Х	
Steering:				
 Power rack-and-pinion steering (speed-sensitive) 	Х	Х	Х	
– Power steering cooler(1)	0	0	Х	
Suspension:				
– Z51 Performance Handling Package(2)	0	0	_	
– F55 Magnetic Selective Ride Control(3)	õ	õ	_	

 Z06 Performance Handling Package Fully independent suspension with transverse springs 	×	- x	X X
<u>Traction:</u> – Active Handling System – Traction Control	X X	X X	X X
Transmission: – 4-speed automatic transmission – 6-speed manual transmission	X O	X O	- x

1 Requires Z51 Performance Handling Package.

2 Not available with F55 Magnetic Selective Ride Control.

3 Standard on 50th Anniversary Edition.

ABACK TO TOP

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

TRAILERING

Trailering is not recommended for Corvette.

▲ВАСК ТО ТОР

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

SEATING

	Coupe	Conv.	Z06
Seating:			
- Seats, leather seating surfaces Z06-specific	:-	_	Х
- Seats, Sport, leather seating surfaces	Х	Х	-
 Seat, power driver, six-way adjustable 	Х	Х	Х
- Seat, power passenger, six-way adjustable	Х	Х	_

BACK TO TOP

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

WHEELS/TIRES

X = Standard. O = Optional. - = Not available.

	Coupe	Conv.	Z06
Wheels:		· •	· · · · · · · · · · · · · · · · · · ·
17" x 8.5" front, 18" x 9.5" rear			
– aluminum	Х	Х	_
 high-polish forged aluminum 	0	0	_
– magnesium(1)	0	0	_
- 50th Anniversary Edition Champagne aluminum(2)	0	0	_
17" x 9.5" front, 18" x 10.5" rear			
– aluminum	-	-	Х
Tires:		· ·	,
Goodyear Eagle F1 GS Extended-Mobility			
– front: P245/45ZR-17	Х	Х	_
– rear: P275/40ZR-18	Х	Х	_
Goodyear Eagle F1 Supercar Non-Extended Mobility	,		
- front: P265/40ZR-17	-	-	Х
– rear: P295/35ZR-18	-	-	Х

NOTE: Do not use tire chains; they can damage your car. 1 Limited availability.

2 Available on 50th Anniversary Edition only.

▲<u>ВАСК ТО ТОР</u>

PREFERRED EQUIPMENT GROUPS (PEGs)

X = Standard. • = Included in Preferred Equipment Groups. – = Not available.

Preferred Equipment Groups are special option packages designed to simplify the buying process. You may also select from the individual options listed throughout this Buyer's Guide. Some restrictions may apply. Please see your dealer for details.

Coupe	1SA	1SB
Head-Up Display	-	•
Electrochromic rearview mirrors: inside and driver's outside	-	•
Memory Package	-	•
Power telescoping and manual Tilt-Wheel steering column	-	•
Twilight Sentinel, Headlamp Control System	-	•

▲<u>BACK TO TOP</u>

1SA	1SB
_	•
_	•
_	•
_	•
_	•



NOTE: 50th Anniversary Edition Preferred Equipment Group 1SC is available on Corvette coupe and convertible models only. Limited availability.

50th Anniversary Edition	1SC
Memory Package	•
Power telescoping and manual Tilt-Wheel steering column	•
Head-Up Display	•
Twilight Sentinel	•
Electrochromic mirrors: inside rearview and outside driver	•
Magnetic Selective Ride Control	•
Champagne aluminum wheels	•
Floor mats with 50th Anniversary logo	•
50th Anniversary fender badging	•
50th Anniversary Red Exterior	•
Shale interior trim	•
Shale convertible top(1)	•

1 Convertible only.

BACK TO TOP

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

CAPACITIES

	Coupe	Convertible	Z06	
Passenger capacity	2	2	2	
Interior Passenger Index (liters/cu. ft.)	1455 / 51.4	Data not available	1464 / 51.7	
Cargo capacity (liters/cu. ft.)	702 / 24.8	394 / 13.9(1)	377 / 13.3	
Liftover height (mm/inches)	934.7 / 36.8			
Fuel tank (liters/gallons) (approximate)	68.1 / 18.0			
Engine oil w/filter (liters/quarts)	6.15 / 6.5			
Engine coolant (liters/quarts)	10.9 / 11.5 (11.2 / 11.8 w/manual trans.)			

1 13.9 cu. ft. with top up; 11.2 cu. ft. with top down.

BACK TO TOP

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

DIMENSIONS

	Coupe	Convertible	Z06	
Exterior				
Wheelbase (mm/in.)	2655.5 / 104.5	2655.5 / 104.5	2655.5 / 104.5	
Length, overall (mm/in.)	4565.6 / 179.7	4565.5 / 179.7	4565.6 / 179.7	
Height, overall (mm/in.)	1211.5 / 47.7	1214.7 / 47.8	1211.5 / 47.7	
Tread Width, front (mm/in.)	1572.3 / 61.9	1572.3 / 61.9	1584.5 / 62.4	
Tread Width rear (mm/in.)	1574.5 / 62.0	1574.5 / 62.0	1589.5 / 62.6	
Interior				
Headroom (mm/in.)	963 / 37.9	955 / 37.6	960 / 37.8	
	7	,	1	

Legroom (mm/in.)	1085 / 42.7	1085 / 42.7
Shoulder Room (mm/in.)	1405 / 55.3	1405 / 55.3
Hip Room (mm/in.)	1377 / 54.2	1377 / 54.2

BACK TO TOP

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

SPECIFICATIONS

Steering Specifications	Coupe	Convertible	Z06
Туре	Speed-sensitive, power-assisted, magnetic variable effort (MagnaSteer)		
Ratio	16.1:1		
Turns, lock-to-lock	2.66 2.46		
Turning Diameter, curb- to-curb (m/ft.)	12/39.4		12.9/42.3
Turning Diameter, wall- to-wall (m/ft.)	12.3/40.3		13.2/43.3
	· · · · · · · · · · · · · · · · · · ·		
Brake Specifications	Coupe	Convertible	Z06
Туре	Four-wheel disc		
Gross Lining, front/rear (sqin)	22.6 / 8.7		
Effective Area, front/rear (sqin)	22.3 / 8.7		
Antilock System	Four-wheel (Bosch ABS V)		
Rotor Dia. x Thickness, front (mm/in.)	325 x 32 / 12.6 x 1.26		
Rotor Dia. x Thickness, rear (mm/in.)	305 x 26 / 12.6 x 1.27		
Swept Area, front, rear	1696 (F) 1018.0 (R) / 263 (F) 158 (R)		

Engine Specifications	Coupe	Convertible	Z06	
Order Code	LS1		LS6	
Туре	Overhead-valve (OHV) Pushrod V8			
Displacement	5.7L/5665 cc	5.7L/5665 cc		
Fuel Induction System	Sequential Fuel Inject	tion		
Horsepower (SAE net @ RPM)	350 @ 5200		405 @ 6000	
Torque (lb.–ft. @ RPM)	375 @ 4400 (manua 360 @ 4000 (automa		400 lbft. @ 4800 (manual)	
Redline (RPM)	6000		6500	
Fuel Shutoff RPM	6200		6600	
Compression Ratio	10.1:1		10.5:1	
Firing Order	1-8-7-2-6-5-4-3		· · ·	
Block	Cast-aluminum 107.1 lbs. (48.6 kg)			
Total Dressed Engine Mass (wt.) Dry	Automatic 457.6 lbs. (208 kg); Manual 497.2 lbs. (226 kg)			
Cylinder Heads	Cast-aluminum 20.3 lbs. (9.2 kg)			
Cylinder Block Length	20.4 in. (519mm)			
Cylinder Head Volume	4.1 cuin. (67.3 cucm)			
Cylinder No. System (front to rear)(1)	1-3-5-7 (L. Bank)			
Head Gasket Thickness (compressed)	1.33mm			
Knock Sensor (number and location)	2 – Valley			
Intake Manifolds	Composite 15.9 lbs. (7.2 kg)			
Exhaust Manifolds	Cast nodular iron			
Valves per Cylinder	2			
Hydraulic Roller Lifters	Standard			
Roller Rocker Arms	Standard			

Crankshaft	Cast iron w/undercut ar	Cast iron w/undercut and rolled fillets			
Camshaft	Hollow steel				
Main Bearing Caps	Powder metal	Powder metal			
Bore x Stroke (in/mm)	3.90 x 3.62 / 99.0 x 92.	0			
Bore Spacing (C/L to C/L)	4.40 in. (111.8mm)				
Cam Drive	Chain				
Tailpipes	4, rear center exit				
Ignition System	Coil near plug				
Battery SAE Capacity	500 cca, 600 cca (Z06)				
Recommended Fuel	Premium unleaded				
Recommended Lubricant	5W/30 Mobil 1 syntheti	5W/30 Mobil 1 synthetic or equivalent			
Recommended Oil Change Interval	15,000 miles or 1 year (Maintenance needs vary with different uses and driving conditions. See the Owner's Manual for more information.)				
Emissions Control (NLEV-Compliant)	Catalytic converter, 3-way catalyst, Air Injector Reaction (AIR), Positive Crankcase Ventilation (PCV)				
Additional Features	Extended-life spark plu monitoring system	Extended-life spark plugs, Extended-life coolant, Oil level sensor, Oil life monitoring system			
1 Rear of engine – drive	takeoff. View from drive ta	keoff end to determine lef	t and right side of engine.		
Transmission Specifications	Coupe /	Convertible	Z06		
Туре	4-speed automatic	6-speed manual	6-speed manual		
Transmission Order Code	M30	MM6	M12		
Gear Ratios:	,	7	·*		
1st	3.06:1	2.66:1	2.97:1		
2nd	1.62:1	1.78:1	2.07:1		
3rd	1.00:1	1.00:1 1.30:1 1.43:1			
4th	0.70:1 1.00:1 1.00:1				

Acceleration Specifications (1)	Coupe	Convertible	Z06	
1 With optional Performance axle (available only with automatic).				
Final Drive Ratio	1.90 (std.) / 2.19 (perf)(1)	1.71	1.92	
Axle Ratio	2.73:1 (std.) 3.15:1 (perf.)(1)	3.42:1	3.42:1	
Reverse	2.29:1	2.90:1	3.28:1	
6th	-	0.50:1	0.56:1	
5th	-	0.74:1	0.84:1	

Specifications (1)			
0–60 mph, Man. Trans. (sec.)	4.6 (manual), 4.9 (auto)		3.9 (manual)
Braking, 60-0 mph (ft.)	125		
Top Speed (kph/mph)(2)	281.6 / 175		275.2 / 171
1/4-mile manual (sec./mph)	13.22 / 109 mph		12.4 / 116
Lateral Acceleration (g)	0.93		1.00
Coefficient of Drag (cd)	0.29	0.33	0.31

1 Data generated during closed-course development testing and provided for reference purposes only. Actual results may vary depending upon equipment, road surfaces, altitudes, temperatures and other variables.

2 Top speed is reached in 5th gear on manual-equipped cars.

▲BACK TO TOP

EXTERIOR | INTERIOR | SOUND SYSTEMS | ENGINE/CHASSIS | TRAILERING | SEATING | WHEELS/TIRES | PREFERRED EQUIPMENT GROUPS | CAPACITIES | DIMENSIONS | SPECIFICATIONS | FUEL ECONOMY

FUEL ECONOMY

Model	LS1 V8 Engine (Coupe)	LS1 V8 Engine (Convertible)	LS6 V8 Engine (Z06)
Manual transmission, estimated MPG(1)	19 city, 28 hwy.	19 city, 28 hwy.	19 city, 28 hwy.
Automatic transmission, estimated MPG(1)	18 city, 25 hwy.	18 city, 25 hwy.	Not applicable
Max. cruising range, (miles)	504 manual/ 450 automatic	504 manual/ 450 automatic	504 manual
Max. cruising range, (kilometers)	811 manual/ 724 automatic	811 manual/ 724 automatic	811 manual

1 Based on GM testing. Official EPA numbers not yet available.

▲<u>BACK TO TOP</u>